



FTR BEARING WHOLESALE LTD

45 mm x 68 mm x 32 mm skf GE 45 TXG3E-2LS Radial spherical plain bearings



GE 45 TXG3E-2LS Bearing 2D drawings and 3D CAD models

Bearing No. GE 45 TXG3E-2LS

Category	Spherical Plain Bearings - Radial
Inventory	0.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight	0.46
EAN	7316572027028
Product Group	B04264
Self Aligning	Yes
Rolling Element	Spherical Plain
Material - Outer Member	Stainless Steel
Material - Ball	Stainless Steel
Material - Liner	Teflon
Relubricatable	No
Enclosure	2 Seals
Other Features	2 Piece Corrosion Resistance Self Lubricating Triple Lip Heavy Duty Seals
Long Description	45MM Bore; 25MM Housing Width; 68MM Outside Diameter; Spherical Plain; Stainless Steel Outer Member; Stainless Steel Ball; Teflon Liner; 32MM Overall Width; Not Relubricatable
Inch - Metric	Metric
Category	Plain Bearings Spherical Radial



FTR BEARING WHOLESALE LTD

UNSPSC	31171515
Harmonized Tariff Code	8483.30.80.70
Noun	Bearing
Keyword 3	Spherical
Keyword String	Plain Spherical Radial
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	GE 45 TXG3E-2LS
Weight / LBS	1.014
Housing Width	0.984 Inch 25 Millimeter
B	1.26 Inch 32 Millimeter
d	1.772 Inch 45 Millimeter
D	2.677 Inch 68 Millimeter
bore diameter:	45 mm
inner ring material:	Steel
outside diameter:	68 mm
outer ring width:	25 mm
misalignment angle:	7 °
race material:	PTFE Composite
inner ring width:	32 mm
overall width:	32 mm
bearing type:	Radial
radial static load capacity:	600 kN
lubrication type:	Maintenance Free/Self-Lubricating
radial dynamic load capacity:	360 kN
closure type:	Triple Lip Seals
operating temperature range:	-50 to +150 ° C ° F
outer ring material:	Stainless Steel
manufacturer upc number:	7316572027028
Lubricant	Maintenance free – dry lubrication



FTR BEARING WHOLESale LTD

Design (sliding contact surface combination)	Steel/PTFE fabric
Sealing solution	Triple-lip seals
d	45 mm
D	68 mm
B	32 mm
C	25 mm
	7 °
d _k	60 mm
r ₁ min.	0.6 mm
r ₂ min.	1 mm
d _a min.	49.5 mm
d _a max.	50.8 mm
D _a min.	61 mm
D _a max.	63.5 mm
r _a max.	0.6 mm
r _b max.	1 mm
Basic dynamic load rating C	360 kN
Basic static load rating C ₀	600 kN
Specific dynamic load factor K	300 N/mm ²
Specific static load factor K ₀	500 N/mm ²
Mass plain bearing	0.04 kg